OMNISCREEN PILOT



DEFENCE AND GOVERMENT



HOSPITALITY



EDUCATION



HEALTH AND AGED CARE

EXPANDING YOUR BUSINESS



PRODUCT FEATURES

Omniscreen Pilot[™] is an enterprise TV and digital signage application server. It is usually provided as an appliance, but can be deployed in the Cloud as a SaaS offering.

Pilot is a versatile entertainment, information, and digital signage solution, which can be customised to most enterprise requirements including Government/corporate offices, broadcast and AV studios, public venues, hospitals and aged care facilities, hotels/resorts, cruise ships, airlines and railways, mining camps, and other locations alike.

Omniscreen Pilot is a reliable solution proven in commercial deployments under 24/7 operating conditions.

KEY FUNCTIONS:









- · Live TV and Pay TV distribution with EPG
- · Playback on TV, PC, tablet, smartphone
- · Network-based video recording
- Personalised content and video/photo sharing
- · Video On-Demand
- · Emergency and general announcements
- · Advertising and Digital Signage
- Scheduling and Playlists

Analogue

- External information feeds (e.g. weather)
- Optional redundant configuration



DVB-S/S2 DVB-C IPTV HEADEND WA N SDI, HD-SDI HDMI HDMI DVB-T/T2 TOTAL TOTAL



OMNISCREEN PILOT

HARDWARE SPECIFICATIONS

DIMENSIONS

Form Factor 1U Rackmount

Height 43mm (1.7")

Width 437mm (17.2") Depth 249mm (9.8")

Weight Net Weight: 3.62kg (8 lbs)

Gross Weight: 5.44kg (12 lbs)

Available Colours Black

ENVIRONMENTAL

RoHS Compliant

Enviromental Spec. Operating Temperature: 10°C to 35°C (50°F to 95°F)

> Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)

Operating Relative Humidity: 8% to 90% (non-condensing)

Non-operating Relative Humidity: 5% to 95% (non-condensing)

FRONT PANEL

Buttons Power On/Off button

System Reset button

LEDs Power LED

Hard drive activity LED 2x Network activity LEDs System Overheat LED


POWER SUPPLY

200W Low Noise AC-DC

power supply with PFC

100 - 240V, 50-60Hz, **AC Voltage**

2.6 Amp Max





All Omniscreen products are very easy to use. Supplied with intuitive web-based interfaces, your system can be potentially used and managed from anywhere via an authorised PC, Mac, tablet or a smartphone.

Microsoft® Active Directory integration is available on request. Authorised users may have different access levels subject to their operational and/or corporate role within the customer organisation.

The end user interface can be customised to reflect corporate identity and branding on all supported devices.

For more information please visit:

www.omniscreen.com.au

or contact our head office: Unit12, 347 Bay Road, Cheltenham, VIC 3192, AUSTRALIA.

Tel: +61 3 8676 5300

© 2013 O7 Technologies Pty Ltd trading as Omniscreen. All specifications are subject to change without notice. Omniscreen is a registered trademark of O7 Technologies Pty Ltd. All other trademarks, products or service names mentioned in this document or Web site are the property of their respective owners. Any references to TV programming, movies and other proprietary content are made only to indicate technical capabilities and are not content offerings.



EXPANDING YOUR BUSINESS

